


### Overview


**HP recommends Windows Vista™  
Business**



1. WLAN Antennas (with WLAN option)
2. RJ-11/modem Port
3. Optical drive
4. Integrated stereo speakers
5. Touchpad with scroll zone
6. Touchpad buttons

7. Hard drive activity LED
8. Battery charging LED
9. Power/standby LED
10. Wireless on/off LED
11. Power button with LED
12. Wireless on/off Button with LED

### Overview



- |                              |                                   |
|------------------------------|-----------------------------------|
| 1. Power connector           | 6. PC Card eject button           |
| 2. 2 USB 2.0 ports           | 7. VGA/external monitor connector |
| 3. Stereo headphone/line out | 8. RJ-45/Ethernet Port            |
| 4. Stereo microphone in      | 9. Kensington Lock slot           |
| 5. Type I/II PC Card slot    |                                   |

### At A Glance

- Genuine Windows Vista Business 32/64, Genuine Windows Vista Home Basic 32, or FreeDOS
- Widescreen 15.4-inch diagonal display with wide-viewing angle, BrightView and HP Privacy Filter support
- Wireless connectivity options:
  - Integrated 802.11a/b/g or 802.11b/g wireless LAN module
  - Bluetooth®
- Intel® Core™2 Duo processor
- Thin, lightweight design starting at 5.7 lb (2.59 kg) and 1.4-inch/34.9 mm thin at front
- Security features including HP ProtectTools Security Manager and Device Access Manager for HP ProtectTools
- Integrated optical drive, including optional DVD+/-RW SuperMulti DL LightScribe Drive
- HP 90W Smart AC Adapter
- Up to 160-GB 5400 rpm user-removable hard drive with HP DriveGuard protection
- Up to 4 GB of 667-MHz DDR2 SDRAM, dual channel memory support
- Mobile Intel Graphics Media Accelerator X3100, with up to 384-MB shared system memory
- Broadcom NetLink Fast Ethernet Controller
- Touchpad with scroll zone

Standard Features

Processors	Intel Core 2 Duo Processor T7700 (2.40-GHz, 800-MHz FSB, 4-MB L2 cache)* Intel Core 2 Duo Processor T7500 (2.20-GHz, 800-MHz FSB, 4-MB L2 cache)* Intel Core 2 Duo Processor T7300 (2.00-GHz, 800-MHz FSB, 4-MB L2 cache)* Intel Core 2 Duo Processor T7100 (1.80-GHz, 800-MHz FSB, 2-MB L2 cache)* <i>* Intel's numbering is not a measurement of higher performance.</i> <b>NOTE:</b> Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.	
Operating System	Preinstalled	Genuine Windows Vista Business 32/64* Genuine Windows Vista Home Basic 32* FreeDOS
	Supported	Genuine Windows XP Professional
	Certified	SuSE Linux Enterprise Desktop 10
	<i>* Certain Windows Vista product features require advanced or additional hardware. See <a href="http://www.microsoft.com/windowsvista/getready/hardwarereqs.mspx">http://www.microsoft.com/windowsvista/getready/hardwarereqs.mspx</a> and <a href="http://www.microsoft.com/windowsvista/getready/capable.mspx">http://www.microsoft.com/windowsvista/getready/capable.mspx</a> for details. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit <a href="http://www.windowsvista.com/upgradeadvisor">http://www.windowsvista.com/upgradeadvisor</a>.</i>	
Chipset	Mobile Intel GM965	
Graphics	Mobile Intel Graphics Media Accelerator X3100, up to 384-MB shared system memory Microsoft DirectX 9 capable	
Display	Internal	15.4-inch diagonal WXGA anti-glare (1280 x 800 resolution and 16M colors) 15.4-inch diagonal WXGA BrightView (1280 x 800 resolution and 16M colors) 15.4-inch diagonal WSXGA+ WVA anti-glare (1680 x 1050 resolution and 16M colors) HP Privacy Filter support
	External	Up to 32-bit per pixel color depth <b>VGA</b> port supports resolutions up to 2048 x 1536 at 75 Hz, and lower resolutions at up to 100 Hz <b>NOTE:</b> Resolutions are dependent upon monitor capability, and resolution and color depth settings.
Memory	Standard	512-MB, 1024-MB, 2048-MB, or 4096-MB 667-MHz DDR2 SDRAM; two SODIMM slots supporting dual channel memory
	Maximum	Upgradeable to 4096-MB maximum (2048-MB SODIMM in slots 1 and 2)
	Dual-channel	Maximized dual-channel performance requires SODIMMs of the same size and speed in both memory slots.
	<b>NOTE:</b> Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.	

Standard Features

Communications	<p>Integrated Broadcom NetLink Fast Ethernet Controller</p> <p>56K V.92 modem*</p> <p>* Designed for downloads from 56K modem compliant sources. Maximum achievable download transmission rates currently do not reach 56 KB/s, and will vary with line conditions. Modem availability is subject to country regulatory approval.</p>												
Wireless Devices	<p>Support for a broad range of secure, integrated wireless LAN options featuring support for the latest industry standards. Wireless LAN is factory configurable or available as an option to be added later. Integrated Bluetooth is also available (factory configurable only) and can be combined with any of the supported wireless LAN options.</p> <table><tr><td>All 802.11a/b/g integrated wireless LAN options</td><td><p>Wi-Fi certified</p><p>Cisco Compatible Extensions support (Version 4.0) with Microsoft Windows XP</p><p>Wired Equivalent Privacy (WEP) support up to 128-bit keys</p><p>Wi-Fi Protected Access (WPA) and WPA2 support</p><p>802.1x authentication support, including EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, and LEAP</p><p>Advanced Encryption Standard (AES) support</p><p>WiFi certified for WPA2, WMM</p><p>Dual antennas integrated in the display enclosure</p></td></tr><tr><td>Intel PRO/Wireless 3945ABG Network Connection*</td><td><p>Integrated support for 802.11 a, b and g</p><p>Up to 54-mbps data rate</p></td></tr><tr><td>Intel PRO/Wireless 3945BG Network Connection*</td><td><p>Integrated support for 802.11 b and g</p><p>Up to 54-mbps data rate</p></td></tr><tr><td>Broadcom 4311AG 802.11a/b/g WiFi Adapter</td><td><p>Integrated support for 802.11 a, b and g</p><p>Up to 54-mbps data rate</p></td></tr><tr><td>Broadcom 4311BG 802.11b/g WiFi Adapter</td><td><p>Integrated support for 802.11 b and g</p><p>Up to 54-mbps data rate</p></td></tr><tr><td>HP Integrated Module with Bluetooth Wireless Technology</td><td><p>Bluetooth Specification v2.0 compliant</p><p>Works with a wide range of Bluetooth devices</p></td></tr></table> <p>* Requires Intel Core 2 Duo processor</p>	All 802.11a/b/g integrated wireless LAN options	<p>Wi-Fi certified</p> <p>Cisco Compatible Extensions support (Version 4.0) with Microsoft Windows XP</p> <p>Wired Equivalent Privacy (WEP) support up to 128-bit keys</p> <p>Wi-Fi Protected Access (WPA) and WPA2 support</p> <p>802.1x authentication support, including EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, and LEAP</p> <p>Advanced Encryption Standard (AES) support</p> <p>WiFi certified for WPA2, WMM</p> <p>Dual antennas integrated in the display enclosure</p>	Intel PRO/Wireless 3945ABG Network Connection*	<p>Integrated support for 802.11 a, b and g</p> <p>Up to 54-mbps data rate</p>	Intel PRO/Wireless 3945BG Network Connection*	<p>Integrated support for 802.11 b and g</p> <p>Up to 54-mbps data rate</p>	Broadcom 4311AG 802.11a/b/g WiFi Adapter	<p>Integrated support for 802.11 a, b and g</p> <p>Up to 54-mbps data rate</p>	Broadcom 4311BG 802.11b/g WiFi Adapter	<p>Integrated support for 802.11 b and g</p> <p>Up to 54-mbps data rate</p>	HP Integrated Module with Bluetooth Wireless Technology	<p>Bluetooth Specification v2.0 compliant</p> <p>Works with a wide range of Bluetooth devices</p>
All 802.11a/b/g integrated wireless LAN options	<p>Wi-Fi certified</p> <p>Cisco Compatible Extensions support (Version 4.0) with Microsoft Windows XP</p> <p>Wired Equivalent Privacy (WEP) support up to 128-bit keys</p> <p>Wi-Fi Protected Access (WPA) and WPA2 support</p> <p>802.1x authentication support, including EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, and LEAP</p> <p>Advanced Encryption Standard (AES) support</p> <p>WiFi certified for WPA2, WMM</p> <p>Dual antennas integrated in the display enclosure</p>												
Intel PRO/Wireless 3945ABG Network Connection*	<p>Integrated support for 802.11 a, b and g</p> <p>Up to 54-mbps data rate</p>												
Intel PRO/Wireless 3945BG Network Connection*	<p>Integrated support for 802.11 b and g</p> <p>Up to 54-mbps data rate</p>												
Broadcom 4311AG 802.11a/b/g WiFi Adapter	<p>Integrated support for 802.11 a, b and g</p> <p>Up to 54-mbps data rate</p>												
Broadcom 4311BG 802.11b/g WiFi Adapter	<p>Integrated support for 802.11 b and g</p> <p>Up to 54-mbps data rate</p>												
HP Integrated Module with Bluetooth Wireless Technology	<p>Bluetooth Specification v2.0 compliant</p> <p>Works with a wide range of Bluetooth devices</p>												
Keyboard	<p>The 101/102-key compatible keyboard features an industry standard, full-pitch key layout with desktop keyboard features, such as the isolated inverted-T cursor control keys, editing keys, both left and right control and alt keys, and 12 function keys. US and International key layouts are available. Other features include an integrated numeric keypad, hotkeys for instant access to power conservation, brightness, and other features, 19-mm x 19-mm key pitch (center-to-center spacing), 2.5-mm stroke, and comfort-dished keycaps.</p>												
Pointing device	<p>Touchpad with scroll zone, two pick buttons</p>												
Expansion card slots	<p>1 Type I/II PC Card slot Supports 32-bit CardBus and 16-bit PC Cards</p>												

### Standard Features

<b>Storage</b>	<b>Hard drives</b>	80/120/160-GB 5400 rpm SMART SATA
	<b>NOTE:</b> These hard drives are customer removable and will withstand multiple insertion/removal cycles. Up to 10 GB is reserved for the system recovery software.	
	<b>HP DriveGuard</b>	The hard drive is mounted directly to the notebook frame, reducing the transmission of shock to the hard drive.
	<b>Fixed optical drives</b>	DVD-ROM Drive DVD/CD-RW Combo Drive DVD+/-RW SuperMulti DL Drive DVD+/-RW SuperMulti DL LightScribe Drive

<b>Interfaces</b>	<b>PC Card slot</b>	One Type I/II PC Card slot
	<b>External monitor</b>	One – VGA
	<b>Stereo microphone in</b>	One
	<b>Stereo headphone/line out</b>	One
	<b>Power connector</b>	One
	<b>RJ-11/modem</b>	One
	<b>RJ-45/Ethernet</b>	One
	<b>USB 2.0</b>	Two
	<b>Secondary battery connector</b>	One
	<b>LED status indicators</b>	Ten

<b>Audio</b>	High Definition Audio support w/24-bit DAC Integrated stereo speakers Stereo headphone/line out Stereo microphone in
--------------	---

<b>Software</b>	<b>Preinstalled software with Windows Vista</b>	PDF Complete HP Backup and Recovery Manager HP Help and Support Center HP Universal Print Driver HP ProtectTools Security Manager: Device Access Manager for HP ProtectTools* HP Quick Launch Buttons HP Wireless Assistant Microsoft Office Ready with 60-day Office Professional 2007 Trial Edition (select models) Roxio Creator 9 for optional DVD+/-RW and DVD/CDRW drives) Synaptics Touchpad Driver Symantec Norton Internet Security with complimentary 60-day live update Intervideo WinDVD – DVD Player
	* Download available from <a href="http://hp.com">hp.com</a> for Windows Vista; preinstalled with Windows XP.	

Standard Features

HP Backup and Recovery Manager	Each unit is shipped with HP Backup and Recovery Manager. HP Backup and Recovery Manager can provide data and system file protection for HP business PCs to enable fast recovery if the system becomes corrupted or if important information is accidentally deleted. HP Backup and Recovery Manager can perform scheduled or manual backups of the entire drive or individual files and folders. Up to 10 GB of the hard drive is reserved for the system recovery software. HP Backup and Recovery Manager can also create software recovery CDs or DVDs (requires optional hardware).
SMBIOS Version 2.4	System Management BIOS, previously known as DMI BIOS, is used to store system management information.
HP ProtectTools Security Manager	HP ProtectTools Security Manager is the security platform for business notebooks and desktops. The HP ProtectTools Security Manager is an extensible client security console that delivers enhanced security capabilities through add-on software modules. Modules currently available are: <ul style="list-style-type: none"><li>• Device Access Manager for HP ProtectTools</li></ul>

Security	<table><tr><td>Standard Features</td><td>HP ProtectTools Security Manager Configuration Control Hardware Memory Change Alert Ownership Tag Setup Password Power-On Password DriveLock HP Disk Sanitizer HP DriveGuard Kensington Lock Slot Support for Computrace / LoJack for Laptops (must be purchased separately)</td></tr><tr><td>Optional Features</td><td>HP Privacy Filter (narrows viewing area)</td></tr><tr><td colspan="2">For more information on HP security solutions refer to <a href="http://www.hp.com/go/security">http://www.hp.com/go/security</a>.</td></tr></table>	Standard Features	HP ProtectTools Security Manager Configuration Control Hardware Memory Change Alert Ownership Tag Setup Password Power-On Password DriveLock HP Disk Sanitizer HP DriveGuard Kensington Lock Slot Support for Computrace / LoJack for Laptops (must be purchased separately)	Optional Features	HP Privacy Filter (narrows viewing area)	For more information on HP security solutions refer to <a href="http://www.hp.com/go/security">http://www.hp.com/go/security</a> .	
Standard Features	HP ProtectTools Security Manager Configuration Control Hardware Memory Change Alert Ownership Tag Setup Password Power-On Password DriveLock HP Disk Sanitizer HP DriveGuard Kensington Lock Slot Support for Computrace / LoJack for Laptops (must be purchased separately)						
Optional Features	HP Privacy Filter (narrows viewing area)						
For more information on HP security solutions refer to <a href="http://www.hp.com/go/security">http://www.hp.com/go/security</a> .							

Power Supply	External 90-watt Smart AC adapter, 6-foot (1.8-meter) power cord included. Total length including external AC adapter is 12 feet (3.66 meter). HP Fast Charge*
*HP Fast Charge recharges your battery up to 90% within 90 minutes when the system is off. HP Fast Charge does not apply to 12-cell Ultra-Capacity batteries.	

Battery	<table><tr><td>Primary battery</td><td>6-cell (55 WHr) Lithium-Ion battery 6-cell (47 WHr) Lithium-Ion battery</td></tr><tr><td>Optional HP Extended Life Battery</td><td>8-cell (52 WHr) high capacity Lithium-Ion battery</td></tr><tr><td>Optional HP Ultra-Capacity Battery</td><td>12-cell (95 WHr) high capacity Lithium-Ion battery</td></tr></table>	Primary battery	6-cell (55 WHr) Lithium-Ion battery 6-cell (47 WHr) Lithium-Ion battery	Optional HP Extended Life Battery	8-cell (52 WHr) high capacity Lithium-Ion battery	Optional HP Ultra-Capacity Battery	12-cell (95 WHr) high capacity Lithium-Ion battery
Primary battery	6-cell (55 WHr) Lithium-Ion battery 6-cell (47 WHr) Lithium-Ion battery						
Optional HP Extended Life Battery	8-cell (52 WHr) high capacity Lithium-Ion battery						
Optional HP Ultra-Capacity Battery	12-cell (95 WHr) high capacity Lithium-Ion battery						

Standard Features

Battery Life		<b>6-cell (55 WHr) Primary</b>	<b>6-cell (47 WHr) Primary</b>
	<b>Primary battery</b>	Up to 5 hours and 15 minutes	Up to 4 hours and 15 minutes
	<b>Primary battery and optional HP Extended Life Battery</b>	Up to 10 hours and 45 minutes	Up to 9 hours and 45 minutes
	<b>Primary battery and optional HP Ultra-Capacity Battery</b>	Up to 14 hours and 30 minutes	Up to 13 hours and 30 minutes
<b>NOTE:</b> The listed battery life measurements were taken on models running Microsoft Windows XP Professional. Battery life will vary depending on the product configuration, product model, applications loaded on the product, power management settings of the product, and the product features used by the customer. As with all batteries, the maximum capacity of this battery will decrease with time and usage.			
System Standby Time	Up to 1 week		
<hr/>			
Power Conservation	Supports enhanced Intel SpeedStep technology with Intel Core 2 Duo processors (allows Battery Optimized Mode, Maximum Performance Mode, or Automatic mode) Intel Display Power Saving technology Hibernation Standby ACPI compliance		
<hr/>			
Service and Support	HP Services offers limited 3-year, 1-year and 90-day warranty options depending on country; 1-year limited warranty on primary battery. On-site service and warranty upgrades are also available. <b>NOTE:</b> Certain restrictions and exclusions apply. Consult the HP Customer Support Center for details. <a href="http://h20000.www2.hp.com/bizsupport/TechSupport/ProductRoot.jsp">http://h20000.www2.hp.com/bizsupport/TechSupport/ProductRoot.jsp</a> .		



### Options

<b>Memory</b>	HP 512-MB (DDR2 667 MHz) SODIMM	EM993AA
	HP 1-GB (DDR2 667 MHz) SODIMM	EM994AA
	HP 2-GB (DDR2 667 MHz) SODIMM	EM995AA
<b>MultiBay II Storage</b> (9.5-mm) <b>NOTE:</b> Requires HP External MultiBay II	HP MultiBay II DVD-ROM Drive	PA849A
	HP MultiBay II DVD/CD-RW Combo Drive	PA850A
	HP MultiBay II DVD+/-RW SuperMulti DL Drive	PA851A
	HP 80-GB 5400rpm MultiBay II Hard Drive	PH357A
<b>Other Storage</b>	HP 80-GB 5400rpm Primary SATA Hard Drive	ET354AA
	HP DVD+/-RW SuperMulti DL LightScribe Drive	ET353AA
	HP Notebooks USB Diskette Drive	DC361B
<b>Communications</b>	Intel Wireless WiFi Link 4965AGN option kit* * Requires Intel Core 2 Duo processor	RT081AA#xxx
<b>Power</b>	HP 2-Bay Battery Charging Station (North America only)	DT533A#xxx
	HP 2-Bay Battery Charging Station (rest of world)	EW424AA#xxx
	HP 10-Bay Battery Charging Station (North America only)	DT534A#ABA
	HP Battery Adapter Kit	PK402A
	HP 90W Smart AC Adapter	ED495AA#xxx
	HP 90W Smart Auto Adapter	ED493AA
	HP 65W AC/Auto/Air Combo Smart Adapter	ED993AA#xxx
	HP 6-Cell Li-Ion Primary Battery	PB994A
	HP 8-cell Extended Life Battery	PB993A
	HP 12-cell Ultra-Capacity Battery	EJ092AA
<b>Carrying Cases</b>	HP Value Nylon Case	RR314AA
	HP Universal Nylon Case	RR315AA
	HP Executive Leather Case	RR316AA
	HP Deluxe Nylon Backpack	RR317AA
	HP Universal Messenger Bag	GD404AA
	HP Deluxe Roller Case	GD405AA
<b>Security</b>	HP PC Card Smart Card Reader with Java Card	EL347AA
	HP ProtectTools Java Card – 10 units	EL348AA
	HP/Kensington MicroSaver Security Lock	PC766A
<b>Input/Output Devices</b>	HP PS/2 Keyboard & Mouse Bundle	RC464AA#xxx
	HP USB Keyboard & Mouse Bundle	RC465AA#xxx
	HP USB/PS2 Optical 2-Button Scroll Mouse	DC369A
	HP USB Optical Travel Mouse	RH304AA
	HP Bluetooth PC Card Mouse	RJ316AA



Memory

Support for up to 4096 MB of 667-MHz DDR2 SDRAM  
Two DIMM slots  
DIMM sizes supported: 512 MB, 1024 MB, and 2048 MB

- Standard Memory
- 512 MB (512 MB x 1)
  - 1024 MB (1024 MB x 1 or 512 MB x 2)
  - 2048 MB (2048 MB x 1 or 1024 MB x 2)
  - 4096 MB (2048 MB x 2)

Optional Memory Upgrades

Support for up to 4096 MB of memory is available (with the installation of optional DDR2 SDRAM memory kits). Both memory slots are user accessible. Please refer to the Hardware and Software Guide for installation procedures. Maximized dual-channel performance requires SODIMMs of the same size and speed in both memory slots.

Up to	Slot 1	Slot 2
1024 MB	1024 MB	Empty
1024 MB	512 MB	512 MB
1536 MB	1024 MB	512 MB
2048 MB	1024 MB	1024 MB
4096 MB	2048 MB	2048 MB

**NOTE:** This chart does not represent all possible memory configurations. Due to the non-industry standard nature of some third-party memory modules, we strongly recommend using only HP branded memory modules to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

Memory Upgrades	HP 512-MB (DDR2 667 MHz) SODIMM	EM993AA
	HP 1024-MB (DDR2 667 MHz) SODIMM	EM994AA
	HP 2048-MB (DDR2 667 MHz) SODIMM	EM995AA

Storage

Removable Media Drive Support

	Quantity Supported	Drive Bay
DVD-ROM Drive	One	Fixed optical drive bay
DVD/CD-RW Combo Drive	One	Fixed optical drive bay
DVD+/-RW SuperMulti DL Drive	One	Fixed optical drive bay
DVD+/-RW SuperMulti DL LightScribe Drive	One	Fixed optical drive bay

Hard Drive Support

	Quantity Supported	Drive Bay
<b>Primary Hard Drives</b>		
160-GB 5400 rpm SMART SATA Hard Drive	One	Dedicated hard drive bay
120-GB 5400 rpm SMART SATA Hard Drive	One	Dedicated hard drive bay
80-GB 5400 rpm SMART SATA Hard Drive	One	Dedicated hard drive bay

Technical Specifications

System Unit	Dimensions (HxWxD)	1.4 in (at front) x 14.1 in x 10.4 in 34.9 mm (at front) x 357.0 mm x 265.0 mm
	Weight	Starting at 5.7 lb (2.59 kg)
<b>NOTE:</b> Height varies depending upon where on the notebook the measurement is made. Weight varies by configuration and components. Weight includes 6-cell battery, 80-GB hard drive, and optical drive. Weight varies by configuration and components.		
Stand-Alone Power Requirements (AC Power)	Nominal Operating Voltage	18.5 V
	Average Operating Power	12.5 W
	Max Operating Power	< 90 W
Temperature	Operating	32° to 95° F (0° to 35° C) (not writing optical) 41° to 95° F (5° to 35° C) (writing optical)
	Non-operating	−4° to 140° F (−20° to 60° C)
Relative Humidity	Operating	10% to 90%, non-condensing
	Non-operating	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature
Shock	Operating	125 G, 2 ms, half-sine
	Non-operating	200 G, 2 ms, half-sine
Random Vibration	Operating	0.75 grms
	Non-operating	1.50 grms
Altitude (unpressurized)	Operating	−50 to 10,000 ft (−15.24 to 3,048 m)
	Non-operating	−50 to 40,000 ft (−15.24 to 12,192 m)
Industry Standard Certifications	UL	Yes
	CSA	Yes
	FCC Compliance	Yes
	Energy Star Compliant	Yes
	ICES	Yes
	GS	Yes
	Australia / NZ A-Tick Compliance	Yes
	CCC	Yes
	Japan VCCI Compliance	Yes
	MIC	Yes
	BSMI	Yes
	CE Marking Compliance	Yes
	BNCI or BELUS	Yes
	CIT	Yes
	GOST	Yes
	Saudi Arabian Compliance (ICCP)	Yes
	SABS	Yes
	UKRSERTCOMPUTER	Yes

Technical Specifications

HP 90W Smart AC Adapter	Dimensions	5.24 x 2.28 x 1.1 in (13.3 x 5.8 x 2.9 cm)	
	Weight	0.86 lb (390 g)	
	Input	100 to 240 VAC	
		Input Efficiency	83% min at 115 VAC
		Input frequency range	47 to 63 Hz
		Input AC current	1.5 A at 90 VAC, 0.75 A at 180 VAC PFC Version
			2.4 A at 90 VAC, 1.2 A at 180 VAC NON PFC Version
	Output	Output power	90W
		DC output	18.5V
		Hold-up time	5 msec at 115 VAC input
		Output current limit	<11A, Over voltage protection- 29V max automatic shutdown
	Connector	3 pin/grounded, mates with interchangeable cords	
	Environmental Design	Operating temperature	32° to 104° F (0° to 40° C)
		Non-operating (storage) temperature	−4° to 149° F (−20° to 65° C)
		Altitude	0 to 10,000 ft (0 to 3,048 m)
		Humidity	20% to 80%
EMI and Safety Certifications		Storage Humidity	10% to 90%
		CE Mark – full compliance with LVD and EMC directives; Worldwide safety standards – IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals – C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE; MTBF- over 200,000 hours at 25°C ambient condition.	

Optional HP Ultra-Capacity Battery	Dimensions (H x W x L)	1.3 x 6.0 x 10.6 in (3.33 x 15.25 x 26.88 cm)	
	Weight	1.77 lb (0.803 kg)	
	Cells/Type	12-cell Lithium-Ion	
	Energy	Watt-hour Capacity	95Wh
	Temperature	Operating (Charging)	32° to 113° F (0° to 45° C)
		Operating (Discharging)	14° to 140° F (−10° to 60° C)
		Non-operating	−4° to 140° F (−20° to 60° C)
	Battery Re-Charge Time	Smart Adapter	3 to 4 hours
		System ON	4 to 5 hours (depending on system power consumption)
	Fuel Gauge	When pressed, LEDs light indicating level of charge remaining on battery	

Technical Specifications

Optional HP Extended Life Battery	Dimensions (H x W x L)	1.0 x 3.9 x 8.7 in (2.5 x 10.0 x 22.0 cm)	
	Weight	1.00 lb (0.455 kg)	
	Cells/Type	8-cell Lithium-Ion	
	Energy	Watt-hour Capacity	52Wh
	Temperature	Operating (Charging)	32° to 113° F (0° to 45° C)
		Operating (Discharging)	14° to 140° F (–10° to 60° C)
		Non-operating	–4° to 140° F (–20° to 60° C)
	Battery Re-Charge Time	System in OFF mode or Standby	3 hours
		System ON	3 to 5 hours (depending on system power consumption)
		HP Fast Charge	Charges the battery up to 90% within 90 minutes when system is OFF
Fuel Gauge	When pressed, LEDs light indicating level of charge remaining on battery		

6-Cell (55WHr) Lithium-Ion battery	Dimensions (H x W x L)	0.8 x 2.1 x 8.0 in (2.0 x 5.3 x 20.3 cm)	
	Weight	0.737 lb (0.335 kg)	
	Cells/Type	6-cell Lithium-Ion	
	Energy	Watt-hour Capacity	55Wh
	Temperature	Operating (Charging)	32° to 113° F (0° to 45° C)
		Operating (Discharging)	14° to 140° F (–10° to 60° C)
		Non-operating	–4° to 140° F (–20° to 60° C)
	Battery Re-Charge Time	System in OFF Mode or Standby	2.5 hours
		System ON	3 to 5 hours (depending on system power consumption)
		HP Fast Charge	Charges the battery up to 90% within 90 minutes when system is OFF

6-Cell (47WHr) Lithium-Ion battery	Dimensions (H x W x L)	0.8 x 2.1 x 8.0 in (2.0 x 5.3 x 20.3 cm)	
	Weight	0.715 lb (0.325 kg)	
	Cells/Type	6-cell Lithium-Ion	
	Energy	Watt-hour Capacity	47Wh
	Temperature	Operating (Charging)	32° to 113° F (0° to 45° C)
		Operating (Discharging)	14° to 140° F (–10° to 60° C)
		Non-operating	–4° to 140° F (–20° to 60° C)
	Battery Re-Charge Time	System in OFF Mode or Standby	2.5 hours
		System ON	3 to 5 hours (depending on system power consumption)
		HP Fast Charge	Charges the battery up to 90% within 90 minutes when system is OFF

Technical Specifications

15.4-inch WSXGA+ wide-viewing angle, anti-glare	Dimensions (W x H)	13.0 x 8.1 in (33.1 x 20.7 cm)	
	Diagonal Size	15.4 in (39.1 cm)	
	Surface Treatment	Anti-glare	
	Number of Colors	Up to 16M	
	Contrast Ratio	300:1 (typical)	
	Refresh Rate	60 Hz	
	Brightness	200 nit (typical)	
	Pixel Resolution	Pitch	0.197 mm
		Format	1680 x 1050
		Configuration	RGB stripe
	Backlight	CCFL	
	PPI	129	
	Viewing Angle	±60° Horizontal, ± 50° Vertical (minimum)	

15.4-inch WXGA anti-glare	Active Area (W x H)	13.0 x 8.1 in (33.1 x 20.7 cm)	
	Diagonal Size	15.4 in (39.1 cm)	
	Surface Treatment	Anti-glare	
	Number of Colors	Up to 16M	
	Contrast Ratio	300:1 (typical)	
	Refresh Rate	60 Hz	
	Brightness	200 nit (typical)	
	Pixel Resolution	Pitch	0.259 mm
		Format	1280 x 800
		Configuration	RGB stripe
	Backlight	CCFL	
	PPI	98	
	Viewing Angle	±30° Horizontal, ±10° Vertical (minimum)	

15.4-inch WXGA BrightView	Active Area (W x H)	13.0 x 8.1 in (33.1 x 20.7 cm)	
	Diagonal Size	15.4 in (39.1 cm)	
	Surface Treatment	BrightView	
	Number of Colors	Up to 16M	
	Contrast Ratio	300:1 (typical)	
	Refresh Rate	60 Hz	
	Brightness	200 nit (typical)	
	Pixel Resolution	Pitch	0.259 mm
		Format	1280 x 800
		Configuration	RGB stripe
	Backlight	CCFL	
	PPI	98	
	Viewing Angle	±30° Horizontal, ±10° Vertical (minimum)	

Hard Drives

Technical Specifications

160-GB 5400 rpm SATA	Drive Weight	0.22 lb (101 g)	
	Capacity	160 GB	
	Height	0.37 in (9.5 mm)	
	Width	2.75 in (70 mm)	
	Interface	ATA-7 / SATA 1.0a	
	Transfer Rate	<b>Synchronous</b> (maximum)	100 MB/s (Drive Capability)
	Seek Time (typical reads, including settling)	<b>Single Track</b>	3 ms
		<b>Average</b>	13ms
		<b>Maximum</b>	24 ms
	Rotational Speed	5400 rpm	
	Logical Blocks	312,581,808	
	Operating Temperature	41° to 140° F (5° to 60° C) [case temp]	
	Features	ATA Security	

120-GB 5400 rpm SATA	Drive Weight	0.22 lb (101 g)	
	Capacity	120 GB	
	Height	0.37 in (9.5 mm)	
	Width	2.75 in (70 mm)	
	Interface	ATA-7 / SATA 1.0a	
	Transfer Rate	<b>Synchronous</b> (maximum)	100 MB/s (Drive Capability)
	Seek Time (typical reads, including settling)	<b>Single Track</b>	3 ms
		<b>Average</b>	13ms
		<b>Maximum</b>	24 ms
	Rotational Speed	5400 rpm	
	Logical Blocks	234,441,648	
	Operating Temperature	41° to 140° F (5° to 60° C) [case temp]	
	Features	ATA Security	

80-GB 5400 rpm SATA	Drive Weight	0.22 lb (101 g)	
	Capacity	80 GB	
	Height	0.37 in (9.5 mm)	
	Width	2.75 in (70 mm)	
	Interface	ATA-7 / SATA 1.0a	
	Transfer Rate	<b>Synchronous</b> (maximum)	100 MB/s (Drive Capability)
	Seek Time (typical reads, including settling)	<b>Single Track</b>	3 ms
		<b>Average</b>	13 ms
		<b>Maximum</b>	24 ms
	Rotational Speed	5400 rpm	
	Logical Blocks	156,301,488	
	Operating Temperature	41° to 140° F (5° to 60° C) [case temp]	
	Features	ATA Security	



Technical Specifications

Removable Storage Drives

DVD-ROM Drive	Access Times	Random	<116 ms CD
			<125 ms DVD
	Max Data Transfer Rate	24X CD-ROM	3,600 KB/s
		8X-DVD	10,800 KB/s
	Transfer Mode	Multiword DMA Mode 2	
	Interface	EIDE	
	Supported Media (read)	CD-DA, CD+(E)G, CD-MIDI, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW	
	Supported Media (write)	None	
	Max Media Capacity (read)	4.7 GB	
	Transport	Tray Loading	
DVD/CD-RW Combo Drive	Access Times	Random	<110 ms CD
			<130 ms DVD
	Max Data Transfer Rate	24X CD-ROM	3,600 KB/s
		8X DVD	10,800 KB/s
		24X CD-R	3,600 KB/s
		24X CD-RW	3,600 KB/s
	Transfer Mode	Multiword DMA Mode 2	
	Interface	EIDE	
	Supported Media (read)	CD-DA, CD+(E)G, CD-MIDI, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW	
	Supported Media (write)	CD-R, CD-RW	
	Max Media Capacity (read)	8.5 GB	
	Max Media Capacity (write)	700 MB	
	Transport	Tray loading	

Technical Specifications

DVD+/-RW SuperMulti DL Drive	Access Times	Random	<175 ms CD <230 ms DVD
	Max Data Transfer Rate	24X CD-ROM	3,600 KB/s
		8X DVD	10,800 KB/s
		24X CD-R	3,600 KB/s
		16X CD-RW	2,400 KB/s
		8X DVD+R	10,800 KB/s
		4X DVD+RW	5,400 KB/s
		8X DVD-R	10,800 KB/s
		4X DVD-RW	5,400 KB/s
		2.4X DVD+R(9)	2,700 KB/s
		5X DVD-RAM	6,750 KB/s
	Transfer Mode	Multiword DMA Mode	
	Interface	EIDE	
	Supported Media (read)	CD-DA, CD+(E)G, CD-MIDI, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW, DVD-RAM	
	Supported Media (write)	CD-R, CD-RW, DVD+R, DVD+RW, DVD-R, DVD-RW, DVD-RAM	
Max Media Capacity (read)	8.5 GB		
Max Media Capacity (write)	8.5 GB		
Transport	Tray Loading		
<hr/>			
DVD+/-RW SuperMulti DL LightScribe Drive	Access Times	Random	<175 ms CD <230 ms DVD
	Max Data Transfer Rate	24X CD-ROM	3,600 KB/s
		8X DVD	10,800 KB/s
		24X CD-R	3,600 KB/s
		16X CD-RW	2,400 KB/s
		8X DVD+R	10,800 KB/s
		4X DVD+RW	5,400 KB/s
		8X DVD-R	10,800 KB/s
		4X DVD-RW	5,400 KB/s
		2.4X DVD+R(9)	2,700 KB/s
		5X DVD-RAM	6,750 KB/s
	Transfer Mode	Multiword DMA Mode	
	Interface	EIDE	
	Supported Media (read)	CD-DA, CD+(E)G, CD-MIDI, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW, DVD-RAM	
	Supported Media (write)	CD-R, CD-RW, DVD+R, DVD+RW, DVD-R, DVD-RW, DVD-RAM, LightScribe	

Technical Specifications

<b>Max Media Capacity</b> (read)	8.5 GB
<b>Max Media Capacity</b> (write)	8.5 GB
<b>Transport</b>	Tray Loading

Audio

<b>Hardware</b>	<b>Implementation</b>	ADI1981HD High Definition CODEC
	<b>Touch-Sensitive Volume Controls</b>	Volume up, volume down, and mute
	<b>Full Duplex</b>	Yes
	<b>Sound Blaster Pro compatible</b>	Yes
	<b>Microphone In</b>	Stereo
	<b>Headphone/Line Out</b>	Stereo

<b>Audio Output Quality</b>	<b>Frequency Response</b>	20 Hz – 20 kHz
	<b>Signal to Noise Ratio</b>	>85 dB
	<b>Total Harmonic Distortion</b>	0.01%
	<b>Noise Floor</b>	-110 dB
	<b>Play/Record Sampling Rate(s)</b>	8 kHz – 48kHz
	<b>DAC</b>	16, 20 or 24-bit
	<b>ADC</b>	16 or 20-bit

<b>Integrated Stereo Speakers</b>	<b>Power Rating</b>	2 Watts
	<b>Impedance</b>	4 Ohms

Communications

Technical Specifications

Integrated Broadcom NetLink Fast Ethernet Controller (10/100 NIC)	Ethernet Features	10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable)
	Power Management	ACPI compliant -- multiple power modes Situation-sensitive features reduce power consumption
	Manageability	Wake-on-LAN from standby and hibernation (configurable; Magic Packet and Microsoft Wake-Up Frame) PXE 2.1 Remote Boot Statistics Gathering (RMON, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)) Comprehensive diagnostic and configuration software suite
	Interface NIC Device Driver Name Drivers Available	PCI Express x1 Broadcom 590x 10/100 Ethernet  Microsoft Windows Vista Microsoft Windows XP

---

V.92 56K Data/Fax Modem	Form Factor	MDC 1.5 Daughtercard
	Power Management Support	APM Revision 1.2, ACPI
	Approvals/Certifications	UL, CSA, NEMKO, CCIB, Industry Canada, FCC Part 68, CTR21, FCC Part 15 Class B, Canadian ICES-003 Class B, C.I.S.P.R.22, Australian ACA, CE Mark, Other Countries
	Data Mode Capabilities	V.92 data V.8bis V.80 V44, V.42bis, MNP5 (Compression) V.42 (LAPM, MNP2-4) (Error Correction) <b>Optional symbol rates:</b> 2800, 3429 Asymmetric Symbol rates <b>Synchronous primary channel data signaling rates:</b> 3600, 31200 Automatic rate re-negotiation V.34 V.32bis V.32 V.23 V.22bis V.22 V.21 Bell 212A Bell 103J

Technical Specifications

	<b>Fax Mode Capabilities</b>	TIA/EIA-578-B (Class 1) T.30, T.4 (Group 3) V.17 V.29 V.27ter V.21 Channel 2
	<b>Command Set</b>	V.250 (Partial) TIA-602 Identification: +GMI, +GMM, +GMR Port control: +IPR, +ICF, +IFC, +ILRR Modulation: +MS, +MR, +MA Error control: +ES, +ER, +EB, +ESR, +ETBM Data compression: +DS, +DR V.251
Intel PRO/Wireless 3945ABG Network Connection	<b>Wireless LAN Standards</b>	IEEE 802.11a IEEE 802.11b IEEE 802.11g
	<b>Interoperability</b>	Wi-Fi certified Cisco Compatible Extensions Program compliant with Microsoft Windows 2000 and XP (details at <a href="http://www.hp.com/go/notebooks/WLAN">http://www.hp.com/go/notebooks/WLAN</a> )
	<b>Frequency Band</b>	2.4 GHz
	<b>Data Rates</b>	802.11b: 1, 2, 5.5, 11 Mbps 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
	<b>Modulation</b>	Direct Sequence Spread Spectrum DBPSK, DQPSK, CCK, OFDM
	<b>Security<sup>1</sup></b>	Supports 64- and 128-bit WEP, WPA, WPA2, hardware-accelerated AES, 802.1x authentication types EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, LEAP, EAP-FAST, EAP-SIM.  Support for Cisco Security Features (proven compatibility with Cisco Aironet infrastructure products through the Cisco Compatible Extensions Program Version 4).
	<b>Sub-channels</b>	Multinational support with frequency bands and channels compliant to local regulations.
	<b>Media Access Protocol</b>	CSMA/CA (Collision Avoidance) with ACK
	<b>Network Architecture Models</b>	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	<b>Roaming</b>	IEEE 802.11 compliant roaming between access points
	<b>Output Power</b> (for CCK) <sup>2</sup>	15 dBm
	<b>Output Power</b> (for OFDM; power varies by data rate) <sup>2</sup>	15 dBm
	<b>Power Consumption</b>	Transmit: 1.8 Watts (max) Receive: 1.4 Watts (max) Idle mode <sup>3</sup> : 150 mW (nominal) Sleep mode: 30 mW (max)
	<b>Power Management</b>	ACPI compliant power management 802.11 compliant power saving mode
	<b>Receiver Sensitivity<sup>4</sup></b>	54 Mbps: -72 dBm, 11 Mbps: -88 dBm , 1 Mbps: -97 dBm
	<b>Antenna Connections</b>	2 U.FL type connectors, 50 ohm nominal impedance

Technical Specifications

Range	802.11 a – Typical (@6 Mbps)	600 feet – Outdoor Open Area 150 feet – Indoor, Office environment
	802.11 b – Typical (@1 Mbps)	1200 feet – Outdoor Open Area 300 feet – Indoor, Office environment
	802.11 g – Typical (@1 Mbps)	1200 feet – Outdoor Open Area 300 feet – Indoor, Office environment
Form Factor	PCI-Express MiniCard	
Weight	0.013 lb (6 g)	
Dimensions	0.19 x 1.2 x 2.0 in (4.75 x 29.85 x 50.8 mm)	
Operating Voltage	3.3V +/- 9%, 1.5V +/- 5%	
Temperature	Operating	32° to 176° F (0° to 80° C)
	Non-operating	–40° to 176° F (–40° to 80° C)
Humidity	Operating	10% to 90% (non-condensing)
	Non-operating	5% to 95% (non-condensing)
Altitude	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 50,000 ft (15,240 m)
Configuration Utility <sup>5</sup>	Microsoft Windows 2000 or XP Choice of Configuration Utility:	
	<ul style="list-style-type: none"><li>• Microsoft Windows XP Wireless Network Connection Manager</li><li>• Intel PROSet for Microsoft Windows 2000 or XP (required for Cisco Compatible Extensions support)</li></ul>	
	Microsoft Windows Vista	
	<ul style="list-style-type: none"><li>• Microsoft Windows Vista Wireless Network Connection Manager</li></ul>	
LED Activity	LED Off – Radio OFF; Solid LED On – Radio ON	
<ol style="list-style-type: none"><li>1. Check latest software/driver release for updates on supported security features.</li><li>2. Maximum output power may vary by country according to local regulations.</li><li>3. In Power Save Polling mode.</li><li>4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).</li><li>5. WLAN supplier's client utility is required for Cisco Compatible Extensions support with Microsoft Windows 2000 or XP. WLAN may also be compatible with certain third-party software supplicants.</li></ol>		

Intel PRO/Wireless 3945BG Network Connection	Wireless LAN Standards	IEEE 802.11b IEEE 802.11g
	Interoperability	Wi-Fi certified Cisco Compatible Extensions Program compliant with Microsoft Windows 2000 and XP (details at <a href="http://www.hp.com/go/notebooks/WLAN">http://www.hp.com/go/notebooks/WLAN</a> )
	Frequency Band	2.4 GHz
	Data Rates	802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
	Modulation	Direct Sequence Spread Spectrum DBPSK, DQPSK, CCK, OFDM
	Security <sup>1</sup>	Supports 64- and 128-bit WEP, WPA, WPA2, hardware-accelerated AES, 802.1x authentication types EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, LEAP, EAP-FAST, EAP-SIM.  Support for Cisco Security Features (proven compatibility with Cisco Aironet infrastructure products through the Cisco Compatible Extensions Program Version 4).
	Sub-channels	Multinational support with frequency bands and channels compliant to local regulations.
	Media Access Protocol	CSMA/CA (Collision Avoidance) with ACK
	Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	Roaming	IEEE 802.11 compliant roaming between access points
	Output Power (for CCK) <sup>2</sup>	15 dBm
	Output Power (for OFDM; power varies by data rate) <sup>2</sup>	15 dBm
	Power Consumption	Transmit: 1.8 Watts (max) Receive: 1.4 Watts (max) Idle mode <sup>3</sup> : 150 mW (nominal) Sleep mode: 30 mW (max)
	Power Management	ACPI compliant power management 802.11 compliant power saving mode
	Receiver Sensitivity <sup>4</sup>	54 Mbps: -72 dBm, 11 Mbps: -88 dBm , 1 Mbps: -97 dBm
	Antenna Connections	2 U.FL type connectors, 50 ohm nominal impedance
	Range	802.11 b – Typical                1200 feet – Outdoor Open Area (@1 Mbps)                          300 feet – Indoor, Office environment  802.11 g – Typical                1200 feet – Outdoor Open Area (@1 Mbps)                          300 feet – Indoor, Office environment
	Form Factor	PCI-Express MiniCard
	Weight	0.013 lb (6 g)
	Dimensions	0.19 x 1.2 x 2.0 in (4.75 x 29.85 x 50.8 mm)
	Operating Voltage	3.3V +/- 9%, 1.5V +/- 5%
	Temperature	Operating                          32° to 176° F (0° to 80° C) Non-operating                      –40° to 176° F (–40° to 80° C)
	Humidity	Operating                          10% to 90% (non-condensing) Non-operating                      5% to 95% (non-condensing)
	Altitude	Operating                          0 to 10,000 ft (3,048 m) Non-operating                      0 to 50,000 ft (15,240 m)



Technical Specifications

Configuration Utility <sup>5</sup>	Microsoft Windows 2000 or XP Choice of Configuration Utility:
	<ul style="list-style-type: none"><li>• Microsoft Windows XP Wireless Network Connection Manager</li><li>• Intel PROSet for Microsoft Windows 2000 or XP (required for Cisco Compatible Extensions support)</li></ul>
	Microsoft Windows Vista
	<ul style="list-style-type: none"><li>• Microsoft Windows Vista Wireless Network Connection Manager</li></ul>
LED Activity	LED Off – Radio OFF; Solid LED On – Radio ON
	<ol style="list-style-type: none"><li>1. Check latest software/driver release for updates on supported security features.</li><li>2. Maximum output power may vary by country according to local regulations.</li><li>3. In Power Save Polling mode.</li><li>4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).</li><li>5. WLAN supplier's client utility is required for Cisco Compatible Extensions support with Microsoft Windows 2000 or XP. WLAN may also be compatible with certain third-party software supplicants.</li></ol>

Broadcom 4311AG 802.11a/b/g WiFi Adapter	Wireless LAN Standards	IEEE 802.11a IEEE 802.11b IEEE 802.11g
	Interoperability	Wi-Fi certified Cisco Compatible Extensions Program compliant with Microsoft Windows 2000 and XP (details at <a href="http://www.hp.com/go/notebooks/WLAN">http://www.hp.com/go/notebooks/WLAN</a> )
	Frequency Band	2.4 GHz and 5 GHz
	Data Rates	802.11b: 1, 2, 5.5, 11 Mbps 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
	Modulation	Direct Sequence Spread Spectrum DBPSK, DQPSK, CCK, OFDM
	Security <sup>1</sup>	Supports 64- and 128-bit WEP, WPA, WPA2, hardware-accelerated AES, 802.1x authentication types EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, LEAP, EAP-FAST.  Support for Cisco Security Features (proven compatibility with Cisco Aironet infrastructure products through the Cisco Compatible Extensions Program Version 4).
	Sub-channels	Multinational support with frequency bands and channels compliant to local regulations.
	Media Access Protocol	CSMA/CA (Collision Avoidance) with ACK
	Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	Roaming	IEEE 802.11 compliant roaming between access points
	Output Power (for CKK) <sup>2</sup>	17.5 dBm
	Output Power (for OFDM; power varies by data rate) <sup>2</sup>	15 dBm
	Power Consumption	Transmit: 2.0 W (max) Receive: 1.5 W (max) Idle mode <sup>3</sup> : 390 mW (nominal) Sleep mode: 20 mW (max)



Technical Specifications

<b>Power Management</b>	ACPI compliant power management 802.11 compliant power saving mode	
<b>Receiver Sensitivity<sup>4</sup></b>	54 Mbps: -72 dBm, 11 Mbps: -88 dBm , 1 Mbps: -97 dBm	
<b>Antenna type</b>	High efficiency dual band antenna with spatial diversity, mounted in the display enclosure	
<b>Range</b>	802.11 a – Typical (@6 Mbps)	600 feet – Outdoor Open Area 150 feet – Indoor, Office environment
	802.11 b – Typical (@1 Mbps)	1200 feet – Outdoor Open Area 300 feet – Indoor, Office environment
	802.11 g – Typical (@1 Mbps)	1200 feet – Outdoor Open Area 300 feet – Indoor, Office environment
<b>Form Factor</b>	PCI-Express MiniCard	
<b>Weight</b>	0.026 lb (12 g)	
<b>Dimensions</b>	0.19 x 1.2 x 2.0 in (4.75 x 29.85 x 50.8 mm)	
<b>Operating Voltage</b>	3.3v +/- 10%	
<b>Temperature</b>	Operating	32° to 176° F (0° to 80° C)
	Non-operating	-40° to 176° F (-40° to 80° C)
<b>Humidity</b>	Operating	10% to 90% (non-condensing)
	Non-operating	5% to 95% (non-condensing)
<b>Altitude</b>	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 50,000 ft (15,240 m)
<b>Configuration Utility<sup>5</sup></b>	Microsoft Windows 2000 or XP Choice of Configuration Utility: <ul style="list-style-type: none"><li>• Microsoft Windows XP Wireless Network Connection Manager</li><li>• Broadcom Wireless Configuration Utility (required for Cisco Compatible Extensions support)</li></ul> Microsoft Windows Vista <ul style="list-style-type: none"><li>• Microsoft Windows Vista Wireless Network Connection Manager</li></ul>	
<b>LED Activity</b>	LED Off – Radio OFF; Solid LED On – Radio ON	

1. Check latest software/driver release for updates on supported security features.
2. Maximum output power may vary by country according to local regulations.
3. In Power Save Polling mode.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).
5. WLAN supplier's client utility is required for Cisco Compatible Extensions support with Microsoft Windows 2000 or XP. WLAN may also be compatible with certain third-party software supplicants.

Broadcom 4311BG	Wireless LAN Standards	
802.11b/g WiFi Adapter	Interoperability	IEEE 802.11b IEEE 802.11g  Wi-Fi certified Cisco Compatible Extensions Program compliant with Microsoft Windows 2000 and XP (details at <a href="http://www.hp.com/go/notebooks/WLAN">http://www.hp.com/go/notebooks/WLAN</a> )
	Frequency Band	2.4 GHz
	Data Rates	802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
	Modulation	Direct Sequence Spread Spectrum DBPSK, DQPSK, CCK, OFDM
	Security <sup>1</sup>	Supports 64- and 128-bit WEP, WPA, WPA2, hardware-accelerated AES, 802.1x authentication types EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, LEAP, EAP-FAST.  Support for Cisco Security Features (proven compatibility with Cisco Aironet infrastructure products through the Cisco Compatible Extensions Program Version 4).
	Sub-channels	Multinational support with frequency bands and channels compliant to local regulations.
	Media Access Protocol	CSMA/CA (Collision Avoidance) with ACK
	Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	Roaming	IEEE 802.11 compliant roaming between access points
	Output Power (for CKK) <sup>2</sup>	17.5 dBm
	Output Power (for OFDM; power varies by data rate) <sup>2</sup>	15 dBm
	Power Consumption	Transmit: 2.0 W (max) Receive: 1.5 W (max) Idle mode <sup>3</sup> : 390 mW (nominal) Sleep mode: 20 mW (max)
	Power Management	ACPI compliant power management 802.11 compliant power saving mode
	Receiver Sensitivity <sup>4</sup>	54 Mbps: -72 dBm, 11 Mbps: -88 dBm , 1 Mbps: -97 dBm
	Antenna type	High efficiency dual band antenna with spatial diversity, mounted in the display enclosure
	Range	802.11 b – Typical (@1 Mbps)      1200 feet – Outdoor Open Area 300 feet – Indoor, Office environment 802.11 g – Typical (@1 Mbps)      1200 feet – Outdoor Open Area 300 feet – Indoor, Office environment
	Form Factor	PCI-Express MiniCard
	Weight	0.026 lb (12 g)
	Dimensions	0.19 x 1.2 x 2.0 in (4.75 x 29.85 x 50.8 mm)
	Operating Voltage	3.3v +/- 10%
	Temperature	Operating                 32° to 176° F (0° to 80° C) Non-operating           -40° to 176° F (-40° to 80° C)
	Humidity	Operating                 10% to 90% (non-condensing) Non-operating           5% to 95% (non-condensing)
	Altitude	Operating                 0 to 10,000 ft (3,048 m) Non-operating           0 to 50,000 ft (15,240 m)

Technical Specifications

Configuration Utility <sup>5</sup>	Microsoft Windows 2000 or XP Choice of Configuration Utility:
	<ul style="list-style-type: none"><li>• Microsoft Windows XP Wireless Network Connection Manager</li><li>• Broadcom Wireless Configuration Utility (required for Cisco Compatible Extensions support)</li></ul>
	Microsoft Windows Vista
	<ul style="list-style-type: none"><li>• Microsoft Windows Vista Wireless Network Connection Manager</li></ul>
LED Activity	LED Off – Radio OFF; Solid LED On – Radio ON
	<ol style="list-style-type: none"><li>1. Check latest software/driver release for updates on supported security features.</li><li>2. Maximum output power may vary by country according to local regulations.</li><li>3. In Power Save Polling mode.</li><li>4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).</li><li>5. WLAN supplier's client utility is required for Cisco Compatible Extensions support with Microsoft Windows 2000 or XP. WLAN may also be compatible with certain third-party software suppliers.</li></ol>

HP Integrated Module with Bluetooth Wireless Technology	Bluetooth Specification	2.0 Compliant
	Dimensions	1.02 x 0.55 x 0.22 in (26 x 14 x 5.7 mm)
	Frequency Band	2402 to 2480 MHz
	Number of Available Channels	79 (1 MHz) available channels
	Data Rates and Throughput	3 Mbps data rate; throughput up to 2.17 Mbps Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric or 1306.9 kbps symmetric
	Transmit Power	-6 dBm to 4 dBm (Bluetooth Class II)
	Receiver Sensitivity	Better than -80 dBm at 0.1 % raw bit error rate
	Power Consumption	Peak (Tx) 264 mW
		Peak (Rx) 231 mW
		Sleep <1 mW
	Antenna	Internally integrated within module
	Range	Up 33 ft (10 m)
	Electrical Interface	USB 2.0 compliant
		Microsoft Windows Plug and Play compliant
	OS Support	Genuine Windows Vista
		Genuine Windows XP
		Genuine Windows 2000
	Bluetooth Software Supported	Broadcom Bluetooth for Windows Microsoft Windows XP Bluetooth Software
	Link Topology	Point to Point, Multipoint Pico Nets up to 7 slaves
	Security	Full support of Bluetooth Security Provisions
	Power Management	Microsoft Windows ACPI, and USB Bus Support
		Self configurable to optimize power conservation in all operating modes, including Standby, Hold, Park, and Sniff
	Certifications	All necessary regulatory approvals for supported countries, including:



Technical Specifications

	FCC (47 CFR) Part 15C, Section 15.247 & 15.249	
	ETS 300 328, ETS 300 826	
	Low Voltage Directive IEC950	
	UL, CSA, and CE Mark	
Temperature	Operating	-4° to 158° F (-20° to 70° C)
	Non-operating	-40° to 176° F (-40° to 80° C)
Humidity	Operating	10% to 90%
	Non-operating	5% to 95%
Altitude	Operating	15,000 ft (4,572 m)
	Non-operating	40,000 ft (12,192 m)
Bluetooth Profiles Supported	(with Bluetooth for Windows 4.0 software)	
	Serial Port Profile (SPP)*	
	Dial-Up Networking (DUN)*	
	Generic Object Exchange Profile (GOEP)	
	Object Push Profile (OPP)*	
	File Transfer Profile (FTP)	
	Synchronization Profile (SYNC)	
	Hard Copy Cable Replacement (HCRP)*	
	Personal Area Networking Profile (PAN)*	
	Human Interface Device Profile (HID)*	
	FAX Profile (FAX)	
	Basic Imaging Profile (BIP)	
	Headset Profile (HSP)	
	Hands Free Profile (HFP)	
	Advanced Audio Distribution Profile (A2DP)	

\* indicates the profile is also supported by Microsoft Windows XP SP2

Copyright © 2007 Hewlett-Packard Development Company, L.P.

All rights reserved. Microsoft, Windows, Windows XP and Windows Vista are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. Core 2 Duo and Celeron are registered trademarks or trademarks of Intel Corporation in the U.S. and/or other countries. Bluetooth is a registered trademark of Bluetooth SIG, Inc., in the U.S. and other countries. All other product names mentioned herein may be trademarks of their respective companies.

The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. The warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.